

Safety Data Sheet

Hempel's Non-Slip Deck Coating



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758 - United Kingdom (UK)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Hempel's Non-Slip Deck Coating
Product identity : 5625122210, 134532
Product type : acrylic paint finishing coat

1.2 Relevant identified uses of the substance or mixture and uses advised against

Field of application : yacht.
Identified uses : Consumer applications, Used by spraying.

1.3 Details of the supplier of the safety data sheet

Company details : Hempel UK Ltd
Berwyn House, The Pavilions
Llantarnam Park
Cwmbran
South Wales NP44 3FD
Telephone: 01633 833600
hempel@hempel.com

1.4 Emergency telephone number

Emergency telephone number (with hours of operation)
UK: **01633 833600** (08.00 - 17.00)
Ireland: **01 809 2166** (National Poisons Information Centre, Monday-Sunday; 08:00-22:00)

See Section 4 of the safety data sheet (first aid measures).

Date of issue : 11 December 2025

Date of previous issue : 27 August 2025.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS

Flam. Liq. 3, H226 FLAMMABLE LIQUIDS
Acute Tox. 4, H332 ACUTE TOXICITY (inhalation)
Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 - Flammable liquid and vapour.
H315 - Causes skin irritation.
H332 - Harmful if inhaled.

Precautionary statements :

General : Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention : Wear protective gloves. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Avoid breathing vapour. Wash thoroughly after handling.

Response : IF INHALED: Call a POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse.

Store locked up.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients : xylene

Supplemental label elements : Contains methyl methacrylate and n-butyl methacrylate. May produce an allergic reaction.

Special packaging requirements

SECTION 2: Hazards identification

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Yes, applicable.

2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT, vPvB or endocrine disruptor.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product/ingredient name	Identifiers	%	GB CLP Classification	Type
ethylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≥25 - ≤50	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315	[1] [2]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	<10	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs)	[1] [2]
dipropylene glycol dibenzoate	REACH #: 01-2119529241-49 EC: 248-258-5 CAS: 27138-31-4	≤2.7	Asp. Tox. 1, H304 Aquatic Chronic 3, H412	[1]
Solvent naphtha (petroleum), light arom.	REACH #: 01-2119455851-35 EC: 918-668-5 CAS: 64742-95-6	≤2.2	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	[1]
toluene	REACH #: 01-2119471310-51 EC: 203-625-9 CAS: 108-88-3 Index: 601-021-00-3	≤0.3	EUH066 Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373	[1] [2]
trimethylolpropane	REACH #: 01-2119486799-10 EC: 201-074-9 CAS: 77-99-6	≤0.3	Asp. Tox. 1, H304 Repr. 2, H361fd	[1]
styrene	REACH #: 01-2119457861-32 EC: 202-851-5 CAS: 100-42-5 Index: 601-026-00-0	≤0.3	Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361d STOT SE 3, H335 STOT RE 1, H372 (hearing organs)	[1] [2]
methyl methacrylate	REACH #: 01-2119452498-28 EC: 201-297-1 CAS: 80-62-6 Index: 607-035-00-6	≤0.3	Asp. Tox. 1, H304 Aquatic Chronic 3, H412 Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317	[1] [2]
n-butyl methacrylate	REACH #: 01-2119486394-28 EC: 202-615-1 CAS: 97-88-1 Index: 607-033-00-5	≤0.3	STOT SE 3, H335 Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	[1]
			STOT SE 3, H335	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit, see section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

General :	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
	If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 112 and give immediate treatment (first aid).
Eye contact :	Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Seek immediate medical attention/advice.
Inhalation :	Remove to fresh air and keep at rest in a position comfortable for breathing. Give nothing by mouth. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately.
Skin contact :	Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. Remove contaminated clothing and shoes.
Ingestion :	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so that vomit will not re-enter the mouth and throat.
Protection of first-aiders :	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact :	No known significant effects or critical hazards.
Inhalation :	Harmful if inhaled.
Skin contact :	Causes skin irritation.
Ingestion :	No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact :	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation :	No specific data.
Skin contact :	Adverse symptoms may include the following: irritation redness
Ingestion :	No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician :	If gasses have been inhaled, from the decomposition of the product, symptoms may be delayed. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments :	No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Extinguishing media :	Recommended: alcohol resistant foam, CO ₂ , powders, water spray. Not to be used : waterjet.
-----------------------	--

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture :	Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Hazardous combustion products :	Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides

5.3 Advice for firefighters

SECTION 5: Firefighting measures

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid all direct contact with the spilled material. Exclude sources of ignition and be aware of explosion hazard. Ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8. No action shall be taken involving any personal risk or without suitable training. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should be used only in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. No sparking tools should be used.

Avoid inhalation of vapour, dust and spray mist. Avoid contact with skin and eyes. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Appropriate personal protective equipment: see Section 8. Always keep in containers made from the same material as the original one.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from: Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

See separate Product Data Sheet for recommendations or industrial sector specific solutions.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Safety Data Sheet

Hempel's Non-Slip Deck Coating



SECTION 8: Exposure controls/personal protection

Product/ingredient name	Exposure limit values
xylene	EH40/2005 WELs (United Kingdom (UK), 1/2020) [xylene, o-,m-,p- or mixed isomers] Absorbed through skin. STEL 15 minutes: 441 mg/m ³ . TWA 8 hours: 50 ppm. TWA 8 hours: 220 mg/m ³ . STEL 15 minutes: 100 ppm.
ethylbenzene	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 552 mg/m ³ . STEL 15 minutes: 125 ppm. TWA 8 hours: 100 ppm. TWA 8 hours: 441 mg/m ³ .
toluene	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 384 mg/m ³ . TWA 8 hours: 191 mg/m ³ . TWA 8 hours: 50 ppm. STEL 15 minutes: 100 ppm.
styrene	EH40/2005 WELs (United Kingdom (UK), 1/2020) STEL 15 minutes: 250 ppm. TWA 8 hours: 100 ppm. TWA 8 hours: 430 mg/m ³ . STEL 15 minutes: 1080 mg/m ³ .
methyl methacrylate	EH40/2005 WELs (United Kingdom (UK), 1/2020) STEL 15 minutes: 416 mg/m ³ . STEL 15 minutes: 100 ppm. TWA 8 hours: 208 mg/m ³ . TWA 8 hours: 50 ppm.

Biological exposure indices

Product/ingredient name	Exposure limit values
xylene	EH40/2005 BMGVs (United Kingdom (UK), 1/2020) [Xylene, o-, m-, p- or mixed isomers] BGV: 650 mmol/mol creatinine, methyl hippuric acid [in urine]. Sampling time: post shift.

Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived effect levels

Not applicable.

Predicted effect concentrations

Not applicable.

8.2 Exposure controls

Appropriate engineering controls

Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Individual protection measures

General :

Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.



Hygiene measures :

Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.

SECTION 8: Exposure controls/personal protection

Eye/face protection :	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Hand protection :	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. The quality of the chemical-resistant protective gloves must be chosen as a function of the specific workplace concentrations and quantity of hazardous substances.
	Since the actual work situation is unknown. Supplier of gloves should be contacted in order to find the appropriate type. Below listed glove(s) should be regarded as generic advice:
	Recommended: Silver Shield / Barrier / 4H gloves, polyvinyl alcohol (PVA), Viton® May be used: nitrile rubber (>0.3 mm) Short term exposure: neoprene rubber (>0.1 mm), butyl rubber (>0.5 mm), natural rubber (latex) (>0.4 mm), polyvinyl chloride (PVC), nitrile rubber (>0.1 mm), butyl rubber (>0.3 mm)
Body protection :	Personal protective equipment for the body should be selected based on the task being performed and the risks involved handling this product. Wear suitable protective clothing. Always wear protective clothing when spraying.
Respiratory protection :	When the product is applied by spraying and for continuous or prolonged work always wear an air-fed respirator e.g. hood with supply of fresh or compressed air or a full face, powered air purifying filter. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If working areas have insufficient ventilation: When the product is applied by means that will not generate an aerosol such as, brush or roller wear half or totally covering mask equipped with gas filter of type A, when grinding use particle filter of type P. (EN140) Be sure to use an approved/certified respirator or equivalent.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state :	Liquid.					
Colour :	Cream					
Odour :	Solvent-like					
pH :	Testing not relevant or not possible due to nature of the product.					
Melting point/freezing point :	Testing not relevant or not possible due to nature of the product.					
Boiling point/boiling range :	Testing not relevant or not possible due to nature of the product.					
Flash point :	Closed cup: 26°C (78.8°F)					
Evaporation rate :	Testing not relevant or not possible due to nature of the product.					
Flammability :	Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.					

Vapour pressure :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
ethylbenzene	9.30076	1.2				

Vapour density :

Not available.

Specific gravity :

1.3 g/cm³

Partition coefficient (LogKow) :

Testing not relevant or not possible due to nature of the product.

Auto-ignition temperature :

Ingredient name	°C	°F	Method
xylene	432	809.6	

Decomposition temperature :

Testing not relevant or not possible due to nature of the product.

Viscosity :

Aspiration hazard (H304) Not classified. Testing not relevant due to nature of the product.

Explosive properties :

Testing not relevant or not possible due to nature of the product.

Oxidising properties :

Testing not relevant or not possible due to nature of the product.

SECTION 9: Physical and chemical properties

9.2 Other information

Solvent(s) % by weight :	Weighted average: 37 %
Water % by weight :	Weighted average: 0 %
VOC content :	477.8 g/l
TOC Content :	Weighted average: 431 g/l
Solvent Gas :	Weighted average: 0.108 m ³ /l

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

The product is stable.

10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5 Incompatible materials

Highly reactive or incompatible with the following materials: oxidising materials.

Reactive or incompatible with the following materials: reducing materials and acids.

10.6 Hazardous decomposition products

When exposed to high temperatures (i.e. in case of fire) harmful decomposition products may be formed:

Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to component solvent vapor concentrations may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headaches, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Accidental swallowing may cause stomach pain. Chemical lung inflammation may occur if the product is taken into the lungs via vomiting.

Acute toxicity

Product/ingredient name	Result	Dose / Exposure	Effects
ethylene	Rabbit - Dermal - LD50 Rat - Oral - LD50 Rat - Inhalation - LC50 Vapour Rat - Inhalation - LC50 Gas. Rat - Oral - LD50	>4200 mg/kg 3523 mg/kg 6350 ppm [4 hours] 5000 ppm [4 hours] 3500 mg/kg	
ethylbenzene	Rabbit - Dermal - LD50 Rat - Oral - LD50	>5000 mg/kg 3914 mg/kg	Liver - Other changes Kidney, Ureter, and Bladder - Other changes
dipropylene glycol dibenzoate	Rat - Dermal - LD50 Rat - Inhalation - LC50 Dusts and mists	>2000 mg/kg >200 mg/l [4 hours]	
Solvent naphtha (petroleum), light arom.	Rat - Oral - LD50	3492 mg/kg	
toluene	Rabbit - Dermal - LD50 Rat - Inhalation - LC50 Vapour Rat - Oral - LD50 Rat - Inhalation - LC50 Vapour Rat - Oral - LD50	3160 mg/kg 6193 mg/m ³ [4 hours] 636 mg/kg >20 mg/l [4 hours] 14100 mg/kg	
trimethylolpropane			Behavioral - Somnolence (general depressed activity) Lung, Thorax, or Respiration - Dyspnea Lung, Thorax, or

Safety Data Sheet

Hempel's Non-Slip Deck Coating



SECTION 11: Toxicological information

styrene	Rat - Oral - LD50 Rat - Inhalation - LC50 Vapour Rat - Inhalation - LC50 Gas. Rat - Oral - LD50	2650 mg/kg 11800 mg/m³ [4 hours] 2770 ppm [4 hours] 7872 mg/kg	Respiration - Respiratory depression Behavioral - Somnolence (general depressed activity) Liver - Other changes
methyl methacrylate	Rabbit - Dermal - LD50	>5 g/kg	Behavioral - Muscle weakness Behavioral - Coma Lung, Thorax, or Respiration - Respiratory depression Skin After systemic exposure - Dermatitis, other
n-butyl methacrylate	Rat - Inhalation - LC50 Vapour Rat - Oral - LD50 Rabbit - Dermal - LD50 Rat - Inhalation - LC50 Gas.	78000 mg/m³ [4 hours] 16 g/kg 11300 µl/kg 4910 ppm [4 hours]	Olfaction - Other changes Eye - Other Lung, Thorax, or Respiration - Dyspnea

Acute toxicity estimates

Product/ingredient name	Oral mg/kg	Dermal mg/kg	Inhalation (gases) ppm	Inhalation (vapours) mg/l	Inhalation (dusts and mists) mg/l
Hempel's Non-Slip Deck Coating					
xylene	3523	3838.0	14193.1	186.1	
ethylbenzene	3500	1100	5000	11	
dipropylene glycol dibenzoate	3914		4500		
Solvent naphtha (petroleum), light arom.	3492	3160			
trimethylolpropane	14100				
styrene	2650			11.8	
methyl methacrylate	7872			78	
n-butyl methacrylate	16000				

Irritation/Corrosion

Product/ingredient name	Result	Species	Exposure
xylene	Rabbit - Eyes - Severe irritant Rabbit - Skin - Moderate irritant	Duration of treatment/exposure: 24 hours Duration of treatment/exposure: 24 hours	Amount/concentration applied: 5 milligrams Amount/concentration applied: 500 milligrams
ethylbenzene	Rabbit - Skin - Irritant Rabbit - Skin - Mild irritant	Duration of treatment/exposure: 24 hours	Amount/concentration applied: 15 milligrams
dipropylene glycol dibenzoate	Rabbit - Respiratory - Mild irritant Rabbit - Eyes - Mild irritant Rabbit - Skin - Mild irritant		
Solvent naphtha (petroleum), light arom.	Rabbit - Eyes - Mild irritant Rabbit - Eyes - Mild irritant Rabbit - Eyes - Mild irritant	Duration of treatment/exposure: 24 hours	Amount/concentration applied: 100 microliters
toluene	Rabbit - Respiratory - Mild irritant Rabbit - Skin - Moderate irritant Rabbit - Eyes - Mild irritant	Duration of treatment/exposure: 0.5 minutes	Amount/concentration applied: 100 mg
styrene	Rabbit - Skin - Moderate irritant Rabbit - Eyes - Moderate irritant	Duration of treatment/exposure: 24 hours	Amount/concentration applied: 20 mg
n-butyl methacrylate	Rabbit - Skin - Irritant Rabbit - Skin - Mild irritant	Duration of treatment/exposure: 24 hours	Amount/concentration applied: 100 milligrams

Sensitiser

No known data available in our database.

Mutagenic effects

No known data available in our database.

Carcinogenicity

No known data available in our database.

Reproductive toxicity

No known data available in our database.

Specific target organ toxicity (single exposure)

Safety Data Sheet

Hempel's Non-Slip Deck Coating



SECTION 11: Toxicological information

Product/ingredient name	Category	Route of exposure	Target organs
Solvent naphtha (petroleum), light arom.	Category 3		Respiratory tract irritation
toluene	Category 3		Narcotic effects
styrene	Category 3		Narcotic effects
methyl methacrylate	Category 3		Respiratory tract irritation
n-butyl methacrylate	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	-	hearing organs
toluene	Category 2	-	-
styrene	Category 1	-	hearing organs

Aspiration hazard

Product/ingredient name	Result
ethylbenzene	ASPIRATION HAZARD - Category 1
Solvent naphtha (petroleum), light arom.	ASPIRATION HAZARD - Category 1
toluene	ASPIRATION HAZARD - Category 1
styrene	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential chronic health effects

No known significant effects or critical hazards.

11.2 Information on other hazards

Other information : No additional known significant effects or critical hazards.

SECTION 12: Ecological information

12.1 Toxicity

Do not allow to enter drains or watercourses.

Product/ingredient name	Result	Species	Exposure
ethylbenzene	Chronic - NOEC - Fresh water	Algae - Green algae - <i>Pseudokirchneriella subcapitata</i>	<1000 µg/l [96 hours]
dipropylene glycol dibenzoate	Acute - LC50	Fish	3.7 mg/l [96 hours]
	Acute - LC50	Daphnia	19.3 mg/l [48 hours]
	Acute - LC50	Algae	1.1 mg/l [72 hours]
Solvent naphtha (petroleum), light arom.	Acute - LC50	Fish - <i>Oncorhynchus mykiss (rainbow trout)</i>	9.22 mg/l [96 hours]
	Acute - EC50	Algae - <i>Pseudokirchneriella subcapitata (green algae)</i>	2.6 mg/l [96 hours]
toluene	Acute - EC50	Daphnia	3.2 mg/l [48 hours]
	Chronic - NOEC - Fresh water	Daphnia - Water flea - <i>Daphnia magna</i>	1000 µg/l [21 days]
	Chronic - NOEC - Fresh water	Algae - Green algae - <i>Pseudokirchneriella subcapitata</i>	<500000 µg/l [96 hours]
styrene	Chronic - NOEC - Fresh water	Algae - Green algae - <i>Pseudokirchneriella subcapitata</i>	63 µg/l [96 hours]
n-butyl methacrylate	Chronic - NOEC - Fresh water	Daphnia - Water flea - <i>Daphnia magna</i> - Neonate	2.6 mg/l [21 days]

12.2 Persistence and degradability

Product/ingredient name	Test	Result
xylene	OECD Ready Biodegradability - Manometric Respirometry Test	>60% [28 days] - Readily 90 - 98% [28 days] - Readily
ethylbenzene		>70% [28 days] - Readily
dipropylene glycol dibenzoate		87% [28 days] - Readily
Solvent naphtha (petroleum), light arom.		>70% [28 days] - Readily
toluene	OECD Ready Biodegradability - Manometric Respirometry Test	>60% [28 days] - Readily 78% [28 days] - Readily
trimethylolpropane	OECD Inherent Biodegradability: Zahn-Wellens/	100% [14 days] - Readily 100% [28 days] - Readily

SECTION 12: Ecological information

styrene	EMPA Test	>60% [10 days] - Readily	
n-butyl methacrylate	OECD Ready Biodegradability - Modified MITI Test (I)	70.9% [28 days] - Readily 88% [28 days] - Readily	
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
xylene			Readily
ethylbenzene			Readily
dipropylene glycol dibenzoate			Readily
Solvent naphtha (petroleum), light arom.			Readily
toluene			Readily
trimethylolpropane			Readily
styrene			Readily
n-butyl methacrylate			Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
xylene	3.12	8.1 - 25.9	Low
ethylbenzene	3.6	-	Low
dipropylene glycol dibenzoate	3.9	-	Low
Solvent naphtha (petroleum), light arom.	-	10 - 2500	High
toluene	2.73	90	Low
trimethylolpropane	-0.47	<1	Low
styrene	2.96	13.49	Low
methyl methacrylate	1.38	-	Low
n-butyl methacrylate	2.99	-	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
xylene	1.6 - 2.6	39 - 365
ethylbenzene	2.2	170.406
toluene	2.1	117.115
trimethylolpropane	1.2	16.5101
styrene	3	896.322
methyl methacrylate	1.2	16.6906
n-butyl methacrylate	1.8	70.2421

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
xylene	No	No	Yes	No	No	No	No
ethylbenzene	No	No	Yes	No	No	No	No
dipropylene glycol dibenzoate	No	No	N/A	No	No	No	No
Solvent naphtha (petroleum), light arom.	No	No	N/A	No	No	No	No
toluene	No	No	Yes	No	No	No	No
trimethylolpropane	No	No	Yes	No	No	No	No
styrene	No	No	Yes	No	No	No	No
methyl methacrylate	No	No	Yes	No	No	No	No
n-butyl methacrylate	No	No	Yes	No	No	No	No

Mobility :

The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Conclusion/Summary : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

The generation of waste should be avoided or minimised wherever possible. Residues of the product is listed as hazardous waste. Dispose of according to all state and local applicable regulations. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Spillage, remains, discarded clothes and similar should be discarded in a fireproof container.

European waste catalogue no. (EWC) is given below.

European waste catalogue (EWC) : 08 01 11*

Packaging

The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 14: Transport information

Transport may take place according to national regulation or ADR for transport by road, RID for transport by train, IMDG for transport by sea, IATA for transport by air.

14.1 UN / ID no.	14.2 Proper shipping name	14.3 Transport hazard class(es)	14.4 PG*	14.5 Env*	Additional information
ADR/RID Class	UN1263 PAINT	3 	III	No.	<u>Tunnel code</u> (D/E)
IMDG Class	UN1263 PAINT	3 	III	No.	<u>Emergency schedules</u> F-E, S-E
IATA Class	UN1263 PAINT	3 	III	No.	-

PG* : Packing group

Env.* : Environmental hazards

14.6 Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorisation - Substances of very high concern

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Not applicable.

Synthetic polymer microparticles - Designation 78

Generic identity of polymer(s) :  Polyolefinic copolymers

Total percentage of synthetic polymer microparticles :  0.1%

Other EU regulations

Seveso category This product is controlled under the Seveso III Directive.

Seveso category

P5c: Flammable liquids 2 and 3 not falling under P5a or P5b

SECTION 15: Regulatory information

15.2 Chemical safety assessment

Consumer use: Chemical Safety Assessments for this product are either complete or not applicable.

SECTION 16: Other information

Abbreviations and acronyms :

ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
EUH statement = CLP-specific Hazard statement
RRN = REACH Registration Number
DNEL = Derived No Effect Level
PNEC = Predicted No Effect Concentration

Full text of abbreviated H statements :

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications [CLP/GHS] :

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Classification	Justification
FLAMMABLE LIQUIDS ACUTE TOXICITY (inhalation) SKIN CORROSION/IRRITATION	On basis of test data Calculation method Calculation method

Notice to reader

 Indicates information that has changed from previously issued version.

The information contained in this safety data sheet is based on the present state of knowledge and EU and national legislation. It provides guidance on health, safety and environmental aspects for handling the product in a safe way and should not be construed as any guarantee of the technical performance or suitability for particular applications.

It is always the duty of the user/employer to ascertain that the work is planned and carried out in accordance with the national regulations.