Hempel's Curing Agent 98000



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758 - United Kingdom (UK)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: Hempel's Curing Agent 98000
Product identity: 9800000000, 0013885E

Product type: curing agent

1.2 Relevant identified uses of the substance or mixture and uses advised against

Field of application: used only as part of two- or multi component products

Ready-for-use mixture : (See base component)

Identified uses: Industrial applications, Used by spraying.

1.3 Details of the supplier of the safety data sheet

Company details : Hempel UK Ltd

Berwyn House, The Pavilions

Llantarnam Park

Cwmbran South Wales NP44 3FD

South Wales NP44 3FD Telephone: 01633 833600 hempel@hempel.com

Date of issue : 27 August 2025

Date of previous issue : 17 January 2024.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition: Mixture

Classification according to UK CLP/GHS

Flam. Liq. 3, H226 FLAMMABLE LIQUIDS

Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION

Eye Dam. 1, H318 SERIOUS EYE DAMAGE/EYE IRRITATION

Skin Sens. 1, H317 SKIN SENSITISATION
Repr. 1B, H360F REPRODUCTIVE TOXICITY

Aquatic Chronic 2, H411 LONG-TERM (CHRONIC) AQUATIC HAZARD See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :











1.4 Emergency telephone number

UK: 01633 833600 (08.00 - 17.00)

Monday-Sunday; 08:00-22:00)

Emergency telephone number (with hours of operation)

Ireland: 01 809 2166 (National Poisons Information Centre,

See Section 4 of the safety data sheet (first aid measures).

Signal word : Danger

Hazard statements: H226 - Flammable liquid and vapour.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage. H360F - May damage fertility.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements:

Prevention: Obtain special instructions before use. Wear protective gloves, protective clothing, eye protection, face

protection, or hearing protection. Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking. Avoid release to the environment.

Response: Collect spillage. IF exposed or concerned: Get medical advice or attention. IF IN EYES: Rinse

cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing. Immediately call a POISON CENTER or doctor.

Hazardous ingredients: polymers with 3-[(2-aminoethyl)amino]propyl Ph silsesquioxanes, methoxy-terminated

3-(2-aminoethylamino)propyltrimethoxysilane

dimethyl dimethoxy silane

Version: 0.07 Page: 1/14



SECTION 2: Hazards identification

Supplemental label elements: Restricted to professional users.

Special packaging requirements

Containers to be fitted with child-

ld- Not applicable.

resistant fastenings:

Tactile warning of danger: Not applicable.

2.3 Other hazards

See Section 15 for details. EU - Substances of very high concern - PBT / vPvB

Other hazards which do not result None known.

in classification:

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product/ingredient name	Identifiers	%	GB CLP Classification	Туре
polymers with 3-[(2-aminoethyl) amino]propyl Ph silsesquioxanes, methoxy-	CAS: 477725-72-7	≥50 - ≤75	Skin Irrit. 2, H315 Eye Dam. 1, H318	[1]
terminated 3-(2-aminoethylamino) propyltrimethoxysilane	EC: 217-164-6 CAS: 1760-24-3	≤5	Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT SE 3, H335	[1]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≤5	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315	[1] [2]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≤3	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304	[1] [2]
dimethyl dimethoxy silane	REACH #: 01-2119976290-35 EC: 214-189-4 CAS: 1112-39-6	≤1	Flam. Liq. 2, H225 Repr. 1B, H360F	[1]
methanol	REACH #: 01-2119433307-44 EC: 200-659-6 CAS: 67-56-1 Index: 603-001-00-X	≤1	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 STOT SE 1, H370 (central nervous system (CNS), eyes) (oral)	[1] [2]
toluene	REACH #: 01-2119471310-51 EC: 203-625-9 CAS: 108-88-3 Index: 601-021-00-3	<1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304	[1] [2]
octamethylcyclotetrasiloxane	REACH #: 01-2119529238-36 EC: 209-136-7 CAS: 556-67-2 Index: 014-018-00-1	≤1	Repr. 2, H361f Aquatic Chronic 1, H410 (M=10)	[1] [3] [4]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Type

- Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit, see section 8.
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EĆ) No. 1907/2006, Annex XIII

SECTION 4: First aid measures

4.1 Description of first aid measures

General: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth

to an unconscious person.

If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 112 and give immediate

treatment (first aid).

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15

minutes, occasionally lifting the upper and lower eyelids. Seek immediate medical attention/advice.

Version: 0.07 Page: 2/14



SECTION 4: First aid measures

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Give nothing by mouth. If

not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention

immediately.

Skin contact : Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or

thinners. Remove contaminated clothing and shoes.

Ingestion: If swallowed, seek medical advice immediately and show this container or label. Keep person warm

and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so

that vomit will not re-enter the mouth and throat.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. If it is suspected that

fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation: No known significant effects or critical hazards.

Skin contact: Causes skin irritation. May cause an allergic skin reaction.

Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain watering redness

Inhalation: Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

stomach pains reduced foetal weight increase in foetal deaths skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician: If gasses have been inhaled, from the decomposition of the product, symptoms may be delayed. Treat

symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested

or inhaled.

Specific treatments: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Extinguishing media: Recommended: alcohol resistant foam, CO₂, powders, water spray.

Not to be used : waterjet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or

mixture:

Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products: Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/

oxides

Version: 0.07 Page: 3/14



SECTION 5: Firefighting measures

5.3 Advice for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid all direct contact with the spilled material. Exclude sources of ignition and be aware of explosion hazard. Ventilate the area. Refer to protective measures listed in sections 7 and 8. No action shall be taken involving any personal risk or without suitable training. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should be used only in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. No sparking tools should be used.

Avoid inhalation of vapour, dust and spray mist. Avoid contact with skin and eyes. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Appropriate personal protective equipment: see Section 8. Always keep in containers made from the same material as the original one.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from: Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

See separate Product Data Sheet for recommendations or industrial sector specific solutions.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Version: 0.07 Page: 4/14

Hempel's Curing Agent 98000



SECTION 8: Exposure controls/personal protection

Product/ingredient name	Exposure limit values
w/lene	EH40/2005 WELs (United Kingdom (UK), 1/2020) [xylene, o-,m-,p- or mixed isomers] Absorbed through skin. STEL 15 minutes: 441 mg/m³. TWA 8 hours: 50 ppm. TWA 8 hours: 220 mg/m³. STEL 15 minutes: 100 ppm.
ethylbenzene	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 552 mg/m³. STEL 15 minutes: 125 ppm. TWA 8 hours: 100 ppm. TWA 8 hours: 441 mg/m³.
methanol	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 333 mg/m³. STEL 15 minutes: 250 ppm. TWA 8 hours: 266 mg/m³. TWA 8 hours: 200 ppm.
toluene	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 384 mg/m³. TWA 8 hours: 191 mg/m³. TWA 8 hours: 50 ppm. STEL 15 minutes: 100 ppm.

Biological exposure indices

Product/ingredient name	Exposure limit values		
Mene	EH40/2005 BMGVs (United Kingdom (UK), 1/2020) [Xylene, o-, m-, p- or mixed isomers] BGV: 650 mmol/mol creatinine, methyl hippuric acid [in urine]. Sampling time: post shift.		

Recommended monitoring procedures

Réference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived effect levels

Product/ingredient name	Type - Population - Exposure	Value	Effects
3-(2-aminoethylamino)propyltrimethoxysilane	DNEL - Workers - Long term - Inhalation	35.5 mg/m³	Effects: Systemic
	DNEL - Workers - Long term - Dermal	5 mg/kg bw/day	Effects: Systemic
xylene	DNEL - Workers - Long term - Inhalation	77 mg/m³	Effects: Systemic
	DNEL - Workers - Long term - Dermal	212 mg/kg bw/day	Effects: Systemic
ethylbenzene	DNEL - Workers - Long term - Dermal	180 mg/kg bw/day	Effects: Systemic
	DNEL - Workers - Long term - Inhalation	77 mg/m³	Effects: Systemic
dimethyl dimethoxy silane	DNEL - Workers - Long term - Inhalation	7.44 mg/kg bw/day	Effects: Systemic
methanol	DNEL - Workers - Long term - Inhalation	260 mg/m ³	Effects: Systemic
	DNEL - Workers - Long term - Dermal	40 mg/kg bw/day	Effects: Systemic
toluene	DNEL - Workers - Long term - Dermal	384 mg/kg bw/day	Effects: Systemic
	DNEL - Workers - Long term - Inhalation	192 mg/m³	Effects: Systemic
octamethylcyclotetrasiloxane	DNEL - Workers - Long term - Inhalation	73 mg/m³	Effects: Systemic

Predicted effect concentrations

Product/ingredient name	Compartment Detail	Value
3-(2-aminoethylamino)propyltrimethoxysilane	Fresh water	0.062 mg/l
	Marine water	0.0062 mg/l
	Sewage Treatment Plant	25 mg/l
	Fresh water sediment	0.22 mg/kg dwt
	Marine water sediment	0.022 mg/kg dwt
	Soil	0.0085 mg/kg dwt
xylene	Fresh water	0.327 mg/l
•	Marine water	0.327 mg/l
	Fresh water sediment	12.46 mg/kg
	Marine water sediment	12.46 mg/kg
	Soil	2.31 mg/kg
	Sewage Treatment Plant	6.68 mg/l
ethylbenzene	Fresh water	0.1 mg/l
•	Marine water	0.01 mg/l

Version: 0.07 Page: 5/14



SECTION 8: Exposure controls/personal protection

	Sewage Treatment Plant	9.6 mg/l
	Fresh water sediment	13.7 mg/kg
	Soil	2.68 mg/kg
dimethyl dimethoxy silane	Fresh water	0.24 mg/l
	Marine water	0.024 mg/l
	Fresh water sediment	0.22 mg/kg
	Marine water sediment	0.022 mg/kg
	Soil	0.053 mg/kg
	Sewage Treatment Plant	10 mg/l
methanol	Fresh water	0.062 mg/l
	Marine water	0.0062 mg/l
	Fresh water sediment	0.22 mg/kg dwt
	Marine water sediment	0.022 mg/kg dwt
	Soil	0.0085 mg/kg dwt
	Sewage Treatment Plant	25 mg/l
toluene	Fresh water	0.68 mg/l
	Marine water	0.68 mg/l
	Sewage Treatment Plant	13.61 mg/l
	Fresh water sediment	16.39 mg/kg
	Marine water sediment	16.39 mg/kg
	Soil	2.89 mg/kg
octamethylcyclotetrasiloxane	Fresh water	1.5 μg/l
	Fresh water	0.15 μg/l
	Sewage Treatment Plant	10 mg/l
	Fresh water sediment	3 mg/kg dwt
	Marine water sediment	0.3 mg/kg dwt
	Soil	0.84 mg/kg dwt

8.2 Exposure controls

Appropriate engineering controls

Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Individual protection measures

General: Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be

worn when soiling is so great that regular work clothes do not adequately protect skin against contact

with the product. Safety eyewear should be used when there is a likelihood of exposure.

Hygiene measures: Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking,

using lavatory, and at the end of day.

Eye/face protection: Safety eyewear complying with an approved standard should be used when a risk assessment

indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face

respirator may be required instead.

Hand protection: Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. The

quality of the chemical-resistant protective gloves must be chosen as a function of the specific

workplace concentrations and quantity of hazardous substances.

Since the actual work situation is unknown. Supplier of gloves should be contacted in order to find the

appropriate type. Below listed glove(s) should be regarded as generic advice:

Recommended: Silver Shield / Barrier / 4H gloves, polyvinyl alcohol (PVA), Viton®

May be used: nitrile rubber (>0.3 mm)

Short term exposure: neoprene rubber (>0.1 mm), butyl rubber (>0.5 mm), natural rubber (latex) (>0.4

mm), polyvinyl chloride (PVC), nitrile rubber (>0.1 mm), butyl rubber (>0.3 mm)

Body protection : Personal protective equipment for the body should be selected based on the task being performed and

the risks involved handling this product.

Wear suitable protective clothing. Always wear protective clothing when spraying.

Chemical-resistant apron.

Respiratory protection : When the product is applied by spraying and for continuous or prolonged work always wear an air-fed

respirator e.g. hood with supply of fresh or compressed air or a full face, powered air purifying filter. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If working areas have insufficient ventilation: When the product is applied by means that will not generate an aerosol such as, brush or roller wear half or totally covering mask equipped with gas filter of type A, when grinding use particle

filter of type P. (EN140) Be sure to use an approved/certified respirator or equivalent.

Environmental exposure controls

Version: 0.07 Page: 6/14



SECTION 8: Exposure controls/personal protection

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : Liquid.

Colour : Transparent

Odour : Non-characteristic.

pH: Testing not relevant or not possible due to nature of the product.

Melting point/freezing point: Testing not relevant or not possible due to nature of the product.

Boiling point/boiling range: Testing not relevant or not possible due to nature of the product.

Flash point : Closed cup: 38°C (100.4°F)

Evaporation rate: Testing not relevant or not possible due to nature of the product.

Flammability: Highly flammable in the presence of the following materials or conditions: open flames, sparks and

static discharge and heat.

Vapour pressure : Vapour Pressure at 20°C Vapour pressure at 50°C

	Vapour i lessure at 20 0			Vap	oui pressui	10 at 50 0
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
methoxy functional phenyl/methyl siloxane	9.75	1.3				

Vapour density : Not available.

Specific gravity : 1.12 g/cm³

Partition coefficient (LogKow): Testing not relevant or not possible due to nature of the product.

Auto-ignition temperature : Not available.

Decomposition temperature: Testing not relevant or not possible due to nature of the product.

Viscosity: Aspiration hazard (H304) Not classified. Testing not relevant due to nature of the product.

Explosive properties: Testing not relevant or not possible due to nature of the product.

Oxidising properties: Testing not relevant or not possible due to nature of the product.

9.2 Other information

Solvent(s) % by weight : Weighted average: 9 % Water % by weight : Weighted average: 0 %

VOC content: 109.6 g/l

TOC Content: Weighted average: 87 g/l
Solvent Gas: Weighted average: 0.027 m³/l

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

The product is stable.

10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5 Incompatible materials

Version: 0.07 Page: 7/14



SECTION 10: Stability and reactivity

Highly reactive or incompatible with the following materials: oxidising materials. Reactive or incompatible with the following materials: reducing materials.

10.6 Hazardous decomposition products

When exposed to high temperatures (i.e. in case of fire) harmful decomposition products may be formed:

Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to component solvent vapor concentrations may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headaches, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Accidental swallowing may cause stomach pain. Chemical lung inflammation may occur if the product is taken into the lungs via vomiting.

Direct contact with the eyes can cause irreversible damage, including blindness.

Acute toxicity

Product/ingredient name	Result	Dose / Exposure	Effects
3 (2-aminoethylamino) propyltrimethoxysilane	Rat - Oral - LD50	2413 mg/kg	
	Rat - Dermal - LD50	>2000 mg/kg	
	Rat - Oral - LD50	866 mg/kg	
	Rabbit - Dermal - LD50	560 mg/kg	
	Rat - Inhalation - LC50 Dusts and	1.49 - 2.44 mg/l [4	
	mists	hours]	
xylene	Rabbit - Dermal - LD50	>4200 mg/kg	
	Rat - Oral - LD50	3523 mg/kg	
	Rat - Inhalation - LC50 Vapour	6350 ppm [4 hours]	
attends are an a	Rat - Inhalation - LC50 Gas.	5000 ppm [4 hours]	Tavia affanta Livan Othan aban na
ethylbenzene	Rat - Oral - LD50	3500 mg/kg	Toxic effects: Liver - Other changes Kidney, Ureter, and Bladder - Other
			changes
	Rabbit - Dermal - LD50	>5000 mg/kg	Changes
dimethyl dimethoxy silane	Rat - Oral - LD50	>2000 mg/kg	
methanol	Rabbit - Dermal - LD50	15800 mg/kg	
eu.ae.	Rat - Oral - LD50	5600 mg/kg	
	Rat - Dermal - LD50	300 mg/kg	
	Rat - Inhalation - LC50 Gas.	64000 ppm [8 hours]	
	Rat - Inhalation - LC50 Gas.	64000 ppm [4 hours]	
toluene	Rat - Oral - LD50	636 mg/kg	
	Rat - Inhalation - LC50 Vapour	>20 mg/l [4 hours]	
octamethylcyclotetrasiloxane	Rat - Oral - LD50	>4800 mg/kg	
	Rat - Dermal - LD50	>2400 mg/kg	
	Rat - Inhalation - LC50 Dusts and	36 mg/l [4 hours]	
	mists		

Acute toxicity estimates

Product/ingredient name	Oral mg/kg	Dermal mg/kg	Inhalation (gases) ppm	Inhalation (vapours) mg/l	Inhalation (dusts and mists) mg/l
Hempel's Curing Agent 98000 xylene	18196.3 3523	17198.3 1100	66781.3 5000	228.7	
ethylbenzene methanol	3500 100	300	4500 64000	11 3	
octamethylcyclotetrasiloxane					36

Irritation/Corrosion

Version: 0.07 Page: 8/14

Hempel's Curing Agent 98000



SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Exposure
polymers with 3-[(2-aminoethyl) amino]propyl Ph silsesquioxanes, methoxy-terminated	Rabbit - Skin - Irritant		
	Rabbit - Eyes - Severe irritant		
3-(2-aminoethylamino) propyltrimethoxysilane	Rabbit - Skin - Mild irritant		
	Rabbit - Eyes - Severe irritant		
xylene	Rabbit - Eyes - Severe irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 5 milligrams
	Rabbit - Skin - Moderate irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 500 milligrams
	Rabbit - Skin - Irritant	•	, and the second
ethylbenzene	Rabbit - Skin - Mild irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 15 milligrams
	Rabbit - Respiratory - Mild irritant Rabbit - Eyes - Mild irritant	·	
dimethyl dimethoxy silane	Rabbit - Eyes - Moderate irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 100 microliters
methanol	Rabbit - Eyes - Moderate irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 100 milligrams
	Rabbit - Skin - Moderate irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 20 milligrams
toluene	Rabbit - Eyes - Mild irritant	Duration of treatment/ exposure: 0.5 minutes	Amount/concentration applied: 100
	Rabbit - Skin - Moderate irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 20 mg
octamethylcyclotetrasiloxane	Rabbit - Eyes - Mild irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 500 milligrams
	Rabbit - Skin - Mild irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 500 milligrams

Sensitiser

Product/ingredient name	Species - Route of exposure	Result
3-(2-aminoethylamino) propyltrimethoxysilane	Guinea pig - skin	Result: Sensitising
propylarinotrioxyonarie	Mouse - skin	Result: Sensitising

Mutagenic effects

No known data avaliable in our database.

Carcinogenicity

No known data avaliable in our database.

Reproductive toxicity

No known data avaliable in our database.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
(2-aminoethylamino)propyltrimethoxysilane methanol toluene	Category 3 Category 1 Category 3	oral	Respiratory tract irritation central nervous system (CNS), eyes Narcotic effects

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
pthylbenzene toluene	Category 2 Category 2	-	hearing organs
toluene	Category 2	-	-

Aspiration hazard

Product/ingredient name	Result
ethylbenzene toluene	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential chronic health effects

Version: 0.07 Page: 9/14



SECTION 11: Toxicological information

No known significant effects or critical hazards.

11.2 Information on other hazards

Other information : No additional known significant effects or critical hazards.

SECTION 12: Ecological information

12.1 Toxicity

Do not allow to enter drains or watercourses. Toxic to aquatic life with long lasting effects.

Product/ingredient name	Result	Species	Exposure
3 (2-aminoethylamino) propyltrimethoxysilane	Acute - LC50	Fish	597 mg/l [96 hours]
	Acute - EC50	Daphnia	81 mg/l [48 hours]
	Acute - EC50	Algae	126 mg/l [72 hours]
ethylbenzene	Chronic - NOEC - Fresh water	Algae - Green algae - Pseudokirchneriella subcapitata	<1000 µg/l [96 hours]
dimethyl dimethoxy silane	Acute - LC50	Fish	>126 mg/l [96 hours]
	Acute - LC50	Daphnia	>119 mg/l [48 hours]
	Acute - LC50	Algae	>118 mg/l [72 hours]
methanol	Chronic - NOEC - Marine water	Algae - Green algae - Ulva pertusa	9.96 mg/l [96 hours]
toluene	Chronic - NOEC - Fresh water	Daphnia - Water flea - Daphnia magna	1000 μg/l [21 days]
	Chronic - NOEC - Fresh water	Algae - Green algae - Pseudokirchneriella subcapitata	<500000 μg/l [96 hours]
octamethylcyclotetrasiloxane	Chronic - NOEC - Fresh water	Daphnia - Water flea - Daphnia magna	1.7 - 15 μg/l [21 days]
	Chronic - NOEC - Fresh water	Fish - Rainbow trout,donaldson trout - Oncorhynchus mykiss - Egg	4.4 μg/l [93 days]
	Acute - LC50	Fish	>0.022 mg/l [96 hours]
	Acute - EC50	Daphnia	0.015 mg/l [48 hours]
	Acute - EC50	Algae	>0.022 mg/l [96 hours]

12.2 Persistence and degradability

Product/ingredient name	Test	Result
(2-aminoethylamino) propyltrimethoxysilane	OECD Ready Biodegradability - DOC Die-Away Test	39% [28 days] - Not readily
xylene		>60% [28 days] - Readily
	OECD Ready Biodegradability - Manometric Respirometry Test	90 - 98% [28 days] - Readily
ethylbenzene		>70% [28 days] - Readily
toluene		100% [14 days] - Readily
octamethylcyclotetrasiloxane	OECD Ready Biodegradability - CO2 in Sealed Vessels (Headspace Test)	3.7% [28 days] - Not readily

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-aminoethylamino) propyltrimethoxysilane xylene ethylbenzene toluene octamethylcyclotetrasiloxane			Not readily Readily Readily Readily Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
3-(2-aminoethylamino)propyltrimethoxysilane	-0.77	-	Low
xylene	3.12	8.1 - 25.9	Low
ethylbenzene	3.6	-	Low
methanol	-0.77	<10	Low
toluene	2.73	90	Low
octamethylcyclotetrasiloxane	6.488	13400	High

12.4 Mobility in soil

Soil/water partition coefficient

Version: 0.07 Page: 10/14

Hempel's Curing Agent 98000



SECTION 12: Ecological information

Product/ingredient name	logKoc	Кос	
3-(2-aminoethylamino)propyltrimethoxysilane	1.54	34.5002	
xylene	1.59	39	
ethylbenzene	2.23	170.406	
dimethyl dimethoxy silane	1.56	36.4191	
methanol	0.44	2.75443	
toluene	2.07	117.115	
octamethylcyclotetrasiloxane	3.49	3064.9	

Results of PMT and vPvM assessment

Product/ingredient name	PMT	Р	М	Т	vPvM	νP	νM
polymers with 3-[(2-aminoethyl)amino]propyl Ph silsesquioxanes, methoxy-terminated	No	No	No	No	No	No	No
3-(2-aminoethylamino)propyltrimethoxysilane	No	No	Yes	No	No	No	Yes
xylene	No	No	Yes	No	No	No	Yes
ethylbenzene	No	No	Yes	Yes	No	No	No
dimethyl dimethoxy silane	No	No	Yes	Yes	No	No	Yes
methanol	No	No	Yes	No	No	No	Yes
toluene	No	No	Yes	Yes	No	No	No
octamethylcyclotetrasiloxane	No	Yes	No	Yes	No	Yes	No

Mobility:

The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

12.6 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

The generation of waste should be avoided or minimised wherever possible. Residues of the product is listed as hazardous waste. Dispose of according to all state and local applicable regulations. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Spillage, remains, discarded clothes and similar should be discarded in a fireproof container.

European waste catalogue no. (EWC) is given below.

European waste catalogue (EWC): 08 01 11*

Packaging

The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 14: Transport information

Transport may take place according to national regulation or ADR for transport by road, RID for transport by train, IMDG for transport by sea, IATA for transport by air.

	14.1 UN / ID no.	14.2 Proper shipping name	14.3 Trans	sport hazard class(es)	14.4 PG*	14.5 Env*	Additional information
ADR/RID Class	UN1263	PAINT	3	₹ 2	111	Yes.	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. Tunnel code (D/E)
IMDG Class	UN1263	PAINT. (octamethylcyclotetrasiloxane (D4))	3	1 1 1 1 2 2	III	Yes.	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. Emergency schedules F-E, S-E
IATA Class	UN1263	PAINT	3		III	Yes.	The environmentally hazardous substance mark may appear if required by other transportation regulations.

Version: 0.07 Page: 11/14



SECTION 14: Transport information

PG*: Packing group

Env.*: Environmental hazards

14.6 Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorisation - Substances of very high concern

Annex XIV

None of the components are listed.

Substances of very high concern

Ingredient name	Intrinsic property	Status	Reference number	Date of revision
octamethylcyclotetrasiloxane octamethylcyclotetrasiloxane	PBT vPvB	Recommended Recommended	10th recommendation 10th recommendation	

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Restricted to professional users.

Other EU regulations

Seveso category This product is controlled under the Seveso III Directive.

Seveso category

Sc: Flammable liquids 2 and 3 not falling under P5a or P5b E2: Hazardous to the aquatic environment - Chronic 2

15.2 Chemical safety assessment

-

SECTION 16: Other information

Abbreviations and acronyms: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

EUH statement = CLP-specific Hazard statement

RRN = REACH Registration Number
DNEL = Derived No Effect Level
PNEC = Predicted No Effect Concentration

Full text of abbreviated H statements: H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour. H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

H331 Toxic if inhaled. H332 Harmful if inhaled.

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

H360F May damage fertility.

H361d Suspected of damaging the unborn child.

H361f Suspected of damaging fertility. H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

Version: 0.07 Page: 12/14



SECTION 16: Other information

Full text of classifications [CLP/GHS] : Acute Tox. 3 Acute Tox. 4 ACUTE TOXICITY - Category 3 Acute Tox. 4 ACUTE TOXICITY - Category 4

Aquatic Chronic 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 Aquatic Chronic 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2

Asp. Tox. 1 ASPIRATION HAZARD - Category 1

Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1

Flam. Liq. 2
Flam. Liq. 2
Flam. Liq. 3
FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3
Repr. 1B
Repr. 2
Repr. 2
Skin Irrit. 2
FLAMMABLE LIQUIDS - Category 2
REPRODUCTIVE TOXICITY - Category 2
Skin Irrit. 2
FLAMMABLE LIQUIDS - Category 3
FLAMMABLE LIQUIDS - Category 1
FLAMMABLE LIQUIDS - Category 2
FLAMMABLE LIQUIDS - Category 3
FLAMMABLE LIQUI

Skin Sens. 1 SKIN SENSITISATION - Category 1
Skin Sens. 1B SKIN SENSITISATION - Category 1B

STOT RE 2 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 1 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1
STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Classification	Justification
FLAMMABLE LIQUIDS SKIN CORROSION/IRRITATION SERIOUS EYE DAMAGE/EYE IRRITATION SKIN SENSITISATION REPRODUCTIVE TOXICITY LONG-TERM (CHRONIC) AQUATIC HAZARD	On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method

Notice to reader

Indicates information that has changed from previously issued version.

The information contained in this safety data sheet is based on the present state of knowledge and EU and national legislation. It provides guidance on health, safety and environmental aspects for handling the product in a safe way and should not be construed as any guarantee of the technical preformance or suitability for particular applications.

It is always the duty of the user/employer to ascertain that the work is planned and carried out in accordance with the national regulations.

Version: 0.07 Page: 13/14

Safe Use of Mixture Information

Hempel's Curing Agent 98000



This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

Indoor or outdoor spray painting by professionals for specialist applications, with good general room ventilation plus respiratory protection

This safe use information is linked to

: Professional spray painting, near-industrial setting

Expert judgment

Sector(s) of use : Industrial uses - Professional uses

Product category(ies) : Coatings and paints, thinners, paint removers

Operational conditions

Place of use : Indoor or outdoor use

Range of application/Process

conditions

Others

: Assumes a good standard of occupational hygiene and safety management has been implemented. Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

: Depending on actual conditions of application. Please consult your local HEMPEL representative

for further advise.

Risk management measures (RMM)

Contributing	Process	Maximum duration	Ventilation		Respiratory	Eye	Hands
activity	category (ies)	duration	Type and air changes per hour				
Preparation of material for application	PROC05	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	Use eye protection according to EN 166.	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Loading of application equipment and handling of coated parts before curing	PROC08b	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	Use eye protection according to EN 166.	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Industrial application of coatings by spraying	PROC07	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	Use a properly fitted, air- purifying or air-fed respirator. EN 14594 with an assigned protection factor of at least 20.	Use eye protection according to EN 166.	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Film formation - force drying, stoving and other technologies	PROC04	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear suitable gloves tested to EN374.
Cleaning	PROC05	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	Use eye protection according to EN 166.	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Waste management	PROC08b	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	Use eye protection according to EN 166.	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

See section 8 of this Safety Data Sheet for specifications.









Page: 14/14