

Hempafloor
Ultimate protection for floors

رغم استخدامنا أحدث تقنيات الطباعة والترسيب، إلا أن اللون في البطاقة قد يختلف عن لون المنتج الأصلي وذلك اعتماداً على المنتج ومقارنته بباقي المنتجات. كما أن تغاوت الألوان قد ينتج عن لمعة الطباعة أو عند إضافة السيليكا مثل السكريد. إذا تحتَّم معرفة اللون الحقيقي للمنتخ ننصح بدهن عيّنة صغيرة قبل القيام بالاختيار النهائي للون المطلوب. كما يجب خلط المجموعات المختلفة قبل استخدامها لتفادى تباين الألوان.

إن دهانات الإيبوكسي سوف يصغرٌ لونها وتتكلّس وتفقد لمعانها معَ مرور الوقت إذا تعرّضت لضوء الشمس المباشر أو المنتشر. واصغرار الدهان هو ظاهرة سطحية سببها أن المادة المكوّنة للدهان تغمق مع الزمن. هذا وتختلف درجة الاصغرار من منتج إلى آخر، ولكن ذلك لا يؤثر على فاعلية وآداء الدهان. وللحماية من أشعة الشمس فوق البنغسجية، نقترح إضافة توب كوت "همبافلور ديورابل ٣٠٠ أو استشارة أحد خبراء همبل للمزيد من الخيارات.

Although we have used the latest in printing and depositing technology, the actual colours may vary in reality depending on the product and when compared across the products. Deviation in colour can also be on account of different gloss and due to addition of Silica as in Screed. For critical colour matches, we recommend to apply on a small area for approval of the colour. Different batches should be blended before use to avoid colour variation.

Epoxy coatings will yellow, chalk and lose gloss over a period of time when exposed to direct or diffused sunlight. Yellowing is a surface phenomenon attributed to the natural darkening of epoxy resin. Degree of yellowing can vary from product to product.

This has no influence on the function and performance of the coating. For UV protection, we suggest you to apply a top coat of Hempafloor Durable 300 or consult Hempel for more suitable ontions.

As a world-leading supplier of trusted coating solutions, Hempel is a global company with strong values, working with customers in the protective, marine, decorative, container and yacht industries. Hempel factories, R&D centres and stock points are established in every region across the globe, Hempel's coatings protect surfaces, structures and equipment. They extend asset lifetimes, reduce maintenance costs and make homes and workplaces safer and more colourful.

Hempel was founded in Copenhagen, Denmark in 1915. It is proudly owned by the Hempel Foundation, which ensures a solid economic base for the Hempel Group and supports cultural, social, humanitarian and scientific purposes around the world

Hempel Qatar

Block 212, Street 16 Salwa Industrial Area P.O.Box 3484, Doha State of Qatar Tel: +974 4455 9000 Fax: +974 4460 0901

Hempel Emirates

Interchange 8
Al Dhaid Road
Plot 698/G, Sajaa Area
P.O.Box 2000, Sharjah
United Arab Emirates
Tel: +971 6 531 0140
Fax: +971 6 531 0141

Hempel Oman

Ghala Industrial Area Beside Komatsu Building No 1280 Way No 5217 P.O. Box 1260, PC 112 Muscat, Sultanate of Oman Tel: +968 24 592759 Fax: +968 24 596895

Hempel Abu Dhabi

Plot No 37, Sector M-15 Mussafah Industrial Area P.O.Box 47006, Abu Dhabi United Arab Emirates Tel: +971 2 5552279 Fax: +971 2 5553379

Hempel Dammam

First Industrial Area First Industrial Area Fourth Road, Bn Zheer Street P.O.Box 1077, Dammam 31431 Kingdom of Saudi Arabia Tel: +966 13 847 1616 Fax: +966 13 847 1816

Hempel Jeddah

Al Suhaili Commercial Centre, Siteen Street, Al Rabwah District, P.O.Box 6783, Jeddah 21452 Kingdom of Saudi Arabia Tel: +966 12 257 4567 Fax: +966 12 275 2828

Hempel Riyadh

Bldg. No. 6371 King Abdulaziz Road P.O.Box 3977, Riyadh 11481 Kingdom of Saudi Arabia Tel: +966 11 497 7839 Fax: +966 11 487 8012

Hempel Bahrain

Mina Salman Industrial Area Building 314, Road 4306, Block 343 P.O.Box 997, Manama Kingdom of Bahrain Tel: +973 1772 8668 Fax: +973 1782 7327

Hempel Kuwait

Shuwaikh Industrial Area Block B, Street No. 30, Plot No. 119 P.O.Box 3400, Safat 13034, State of Kuwait Tel: +965 2 202 0700 Fax: +965 2 484 3307













Think Green, Go Paperless

Ver 3 -10.202

Hempafloor colours

Hempafloor is Hempel's complete floor coating systems solution. Its highly technological and innovative formulas are designed to maximize your floor protection. The following are the standard recommended colours, but it can be tinted in other colours upon request.

